

# LISO FLOOR 4000

Transparent and color Protection for Wooden floors



The green power  
for your surfaces

## CHARACTERISTICS

LisoFloor 4000 consists of reactive polymers. This water-based solution is an excellent protection for wood floors, both indoors and outdoors.

## PRODUCT DESCRIPTION

LisoFloor 4000 complies with VOC standards worldwide. LisoFloor 4000, while giving a satin or glossy finish, colored or not, protects your wooden floor. Easy application with a roller.

Excellent durability of this protection. Strong increase in wear resistance. Does not flake or discolor.

Aqueous solution product, without any solvent and with a very low VOC emission rate.

Interior or exterior use. For all types of wood. Do not polish or burnish this product.

### LisoChem SRL

Rue de Le Mesnil, 34  
5670 Viroinval (Belgium)  
Phone: +32 60 490 190  
Mobile: +32 483 367 323  
[www.lisochem.com](http://www.lisochem.com)  
[info@lisochem.com](mailto:info@lisochem.com)

### Manufacture & Office

Rue des Mousquetaires Gris 35  
ZI de Mariembourg  
5660 Belgium  
Phone: +32 60 490 190  
Mobile: + 32 483 367 323

# LISO FLOOR 4000

Transparent and color Protection for Wooden floors

*The Green Power for your Surfaces*

## CHARACTERISTICS

LisoFloor 4000

- Product based on a set of new water-based resins.
- Excellent resistance to abrasion and dust.
- Excellent hydrophobicity and oleophobicity of the surface.
- Aqueous solution product, without any solvent and with a very low VOC emission rate.

## PRODUCT DESCRIPTION

LisoFloor 4000 complies with VOC standards worldwide. LisoFloor 4000 while giving a satin or glossy finish, colored or not, protects your wooden floor. Easy application with a roller.

Excellent durability of this protection. Strong increase in wear resistance. Does not flake or discolor. Aqueous solution product, without any solvent and with a very low VOC emission rate.

Interior or exterior use. For all types of wood. Do not polish or burnish this product.

The treated surface will be accessible to pedestrians after 3 days and to all traffic 8 days after application.

## SECURITY

For more information, please refer to the safety data sheet :

- » Keep out of reach of children
- » Protect from frost
- » Wear gloves and safety glasses
- » Cover all metal and glass parts before application

## PHYSICAL PROPERTIES

Milky liquid, aqueous solution

Active ingredients : 100%

Boiling point : 100°C

Freezing point : 0°C

Shelf life : 1 year in original closed container and stored in a closed place under normal conditions.

# LISO FLOOR 4000

Transparent and color Protection for Wooden floors

*The Green Power for your Surfaces*

## PREPARATION, APPLICATION, MAINTENANCE

### General remarks

- Never apply in frost or rain. Always test on the substrate in an inconspicuous place.
- Never dilute or add other products or liquids to the base product. It is very important to mix Liso-Floor 4000 before and during use.

### Preparation & Application (Refer to application system)

### Maintenance

Try to clean your surface at least once a week with neutral soap during the first month of application. This will increase the hardness and resistance to various stains such as oil, drinks, etc.

## EQUIPMENT

- » Vacuum cleaner
- » Roller

## PACKAGING

Only Bucket ..... 20L