

LISOFLOOR 2000

Satin-finish solid color and available in non-slip



The green power
for your surface

CHARACTERISTICS

LisoFloor 2000 is a solid color for concrete floors. This easy-to-use, roller-applied solution, based on various resins, will give you a satin finish and is also available in anti-slip quality.

PRODUCT DESCRIPTION

Acrylic resin-based product for new or old concrete surfaces that, after 5 days, gives you excellent abrasion resistance, a dust-free surface, excellent waterproofing and resistance to many chemicals (such as oil, citrus juice, milk, vinegar and water).

Aqueous solution product, with very low VOC emissions.

LisoChem SRL

Rue de Le Mesnil, 34
5670 Viroinval (Belgium)
Phone: +32 60 490 190
Mobile: +32 483 367 323
www.lisochem.com
info@lisochem.com

Manufacture & Office

Rue des Mousquetaires Gris 35
ZI de Mariembourg
5660 Belgium
Phone: +32 60 490 190
Mobile: + 32 483 367 323

LISO FLOOR 2000

Satin-finish solid color and available in non-slip

The Green Power for your surface

BENEFITS

LisoFloor 2000 :

- Acrylic resin-based product
- For new and old concrete surfaces
- Excellent abrasion and dust resistance
- Excellent waterproofing and resistance to a wide range of chemicals, and also available in an anti-slip version
- Water-based product, with very low VOC emissions

USE

New or old concrete

For medium traffic: pedestrian

Caution! Not recommended for heavy traffic (cars, parking lots),

SECURITY

Please refer to the safety data sheet :

- Keep out of reach of children
- Protect from freezing
- Wear gloves and safety glasses
- Cover all metal and glass parts before application

PROPERTIES

Boiling point : 100°C

Color : 5 RAL available

Density : 1,1


Shelf life: 6 months in original, closed container

LISO FLOOR 2000

Satin-finish solid color and available in non-slip.

The Green Power for your surface

COLORS



RAL 9003



7016



7040



7037



7035

PREPARATION, APPLICATION

General notes :

- Never apply in frost or rain. Never dilute or add other products or liquids to the base product.
- It is very important to mix LisoFloor products thoroughly before and during use.
- Never polish or buff the surface!

Preparation and application : (See application system)

Never apply when it's freezing, raining or very hot. Ideal temperature between 8° C and 27° C.

- Clean surface several times with vacuum cleaner and scrubber-dryer.
- Mix well
- Apply a 1st coat with a roller (approx. 8 m²/L)
- Allow to dry for at least 45 minutes
- Apply 2nd coat by roller (approx. 10 m²/L)
- Allow to dry for at least 45 minutes
- Apply a 3rd coat according to desired color
- Allow to dry for at least 24 hours for pedestrian traffic and 7 to 8 days for heavier traffic and optimum efficiency

PACKAGING

Bucket20L

Lisochem S.R.L. Tous droits réservés.
Date de révision : 15-05-2024