

LISOTOP 550

The perfect protection for all types of wood



The green power
for your surface

CHARACTERISTICS

LisoTop 550 is a colorless, waterproofing treatment for all types of wood used indoors and outdoors.

- Transparent product that does not alter surface appearance
- Good permeability too water vapor transmission

PRODUCT DESCRIPTION

LisoTop 550 is a high-performance, water-based fluoropolymer designed to give superior oil and water repellency to all interior and exterior wood surfaces.

LisoTop 550 is non-toxic, odorless, water-based, non-flammable and easy to use. The product is designed to penetrate deep into wood fibers without altering appearance.

Treated surfaces are easy to clean. No risk of delamination or wear of the protection..

LisoChem SRL

Rue de Le Mesnil, 34
5670 Viroinval
(Belgium)

Phone: +32 60 490 190
Mobile: +32 483 367 323
www.lisochem.com
info@lisochem.com

Manufacture & Office

Rue des Mousquetaires Gris
35 ZI de Mariembourg
5660 Belgium
Phone: +32 60 490 190
Mobile: + 32 483 367 323

LISOTOP 550

The perfect protection for all types of wood

The Green Power for your surface

BENEFITS

LisoTop 550 :

- Is a colorless, waterproofing, oil-repellent treatment for all types of wood, indoors and out.
- Is a new, exclusive product based on latest-generation fluorinated polymers.
- Water-based product.

USE

LisoTop 550 is suitable for all types of interior and exterior wood.

SECURITY

Please refer to the safety data sheet:

- Keep out of reach of children
- Protect from freezing
- Wear gloves and safety glasses
- Cover all metal and glass parts before application

PROPERTIES

- Transparent or slightly yellowish liquid
- Odorless
- Boiling point : 100°C
- Shelf life: 1 year in unopened original packaging

LISOTOP 550

The perfect protection for all types of wood

The Green Power for your surface

PREPARATION, APPLICATION, MAINTENANCE

General notes :

- Never apply in frost or rain. Always test on the substrate in an inconspicuous place.
- Never dilute or add other products or liquids to the base product. It is very important to mix the product thoroughly before and during use.

Preparation and application :

Always test on the substrate in an inconspicuous place.

- LisoTop 550 should be applied using a low-pressure sprayer, airless, roller or brush.
- Apply 1 liter of product for 7 to 10 m². Yield varies according to surface porosity.
- Apply a first coat and, before drying, a second coat.
- Never leave an excess of product; wipe with a clean cloth before drying.
- For vertical surfaces, always apply the product from bottom to top.
- Maximum protection is achieved 3 to 6 days after treatment.

Please read the application system.

Care : Clean all equipment with water.

PACKAGING

Bucket20L

IBC.....1000L

Lisochem S.R.L. Tous droits réservés.
Date de révision : 15-05-2024